

PALM Intranet

Application  
Number 

IDS Flag Clearance for Application 10699870

Content	Mailroom Date	Entry Number	IDS Review	Last Modified	Reviewer
M844	2005-12-07	18	Y <input checked="" type="checkbox"/>	2006-04-13 16:29:30.0	EBurns
M844	2005-03-11	15	Y <input checked="" type="checkbox"/>	2006-04-13 16:29:29.0	EBurns
<input type="button" value="Update"/>					

10/699, 870

## Refine Search

## Search Results -

Terms	Documents
L21 and L15	0

Database:

US Pre-Grant Publication Full-Text Database  
 US Patents Full-Text Database  
 US OCR Full-Text Database  
 EPO Abstracts Database  
 JPO Abstracts Database  
 Derwent World Patents Index  
 IBM Technical Disclosure Bulletins

701/208

Search:

L22

Refine Search

Recall Text

Clear

Interrupt

## Search History

 DATE: Monday, November 13, 2006   [Purge Queries](#)   [Printable Copy](#)   [Create Case](#)

<u>Set</u> <u>Name</u>	<u>Query</u>	<u>Hit</u> <u>Count</u>	<u>Set</u> <u>Name</u> result set
DB=PGPB,USPT,USOC,EPAB,JPAB,DWPI,TDBD; THES=ASSIGNEE; PLUR=YES; OP=OR			
<u>L22</u>	L21 and l15	0	<u>L22</u>
<u>L21</u>	l18 or l19 or l20	18	<u>L21</u>
DB=USPT; THES=ASSIGNEE; PLUR=YES; OP=OR			
<u>L20</u>	(5974357   5874905   5378969   5559707   5802492   5832406   5471205   5168452   5638116   5113185   5982301):[PN]	11	<u>L20</u>
<u>L19</u>	("6148090")[PN]	1	<u>L19</u>
<u>L18</u>	("6148090")[URPN]	6	<u>L18</u>
DB=PGPB,USPT,USOC,EPAB,JPAB,DWPI,TDBD; THES=ASSIGNEE; PLUR=YES; OP=OR			
<u>L17</u>	6148090.pn.	2	<u>L17</u>
<u>L16</u>	6418090.pn.	2	<u>L16</u>
<u>L15</u>	L14 and 701/209.ccls.	57	<u>L15</u>

<u>L14</u>	l12 or L13	1225	<u>L14</u>
<u>L13</u>	L11 and @pd<=20030107	734	<u>L13</u>
<u>L12</u>	L11 and @ad<=20030107	1223	<u>L12</u>
<u>L11</u>	L10 and map\$ and navigation\$	1923	<u>L11</u>
<u>L10</u>	(extract\$ with (string\$ or character\$ or data)) same (display\$ or screen\$) <i>DB=PGPB,USPT,USOC; THES=ASSIGNEE; PLUR=YES; OP=OR</i>	34151	<u>L10</u>
<u>L9</u>	L8 or L7	10	<u>L9</u>
<u>L8</u>	L6 and @pd<=20001027	7	<u>L8</u>
<u>L7</u>	L6 and @ad<=20001027	10	<u>L7</u>
<u>L6</u>	L5 AND (GIFT\$ OR PRESENTS) and ((single or one\$) with order\$)	14	<u>L6</u>
<u>L5</u>	L2 OR L4 (5963915   5898594   2002/0010623   6094681   6016504   5970474   5774874   6128663   6360254   5113496   5754981   6393490   5826039   5895468)! [PN]	23	<u>L5</u>
<u>L4</u>	5774874   6128663   6360254   5113496   5754981   6393490   5826039   5895468)! [PN]	13	<u>L4</u>
<u>L3</u>	('6609106') [PN]	1	<u>L3</u>
<u>L2</u>	('6609106') [URPN]	10	<u>L2</u>
<u>L1</u>	6609106.PN.	1	<u>L1</u>

END OF SEARCH HISTORY

[First Hit](#) [Fwd Refs](#)[Previous Doc](#)[Next Doc](#)[Go to Doc#](#)

Generate Collection

Print

L23: Entry 1 of 3

File: USPT

Nov 14, 2000

DOCUMENT-IDENTIFIER: US 6148090 A

TITLE: Apparatus and method for providing map information in image formAbstract Text (1):

An apparatus for providing map information includes a route calculating module for extracting crossing information on a map, a navigation guidance generating module for generating images near the crossing extracted and a rally map generating module for disposing the generated images near the crossing in fixed sequence, and is constructed to output the images of the crossing disposed in the fixed sequence. Therefore, even if a personal computers are not provided with the same software and a navigation apparatus made by the same manufacturer and a portable computer are not carried, it is able to provide the apparatus for providing map information that is possible to provide or use easily to understand searched route information.

Application Filing Date (1):

19971110

DATE ISSUED (1):

20001114

Brief Summary Text (3):

The present invention relates to an apparatus for providing map information to a user by printing out the map information or displaying it on a display apparatus, a method for providing the map information and information recording medium.

Brief Summary Text (5):

Conventionally, in a personal computer provided with map display and route searching software and a navigation apparatus (including not only a car navigation apparatus but also a portable navigation apparatus), for example, in the case of searching for a route and providing the searched route to others, the route data obtained by searching is recorded to, for example, a medium such as a memory card or a floppy disk, and is supplied to a personal computer having the same software or a navigation apparatus (a compatible apparatus) made by the same manufacturer and is reproduced.

Brief Summary Text (6):

However, such route data can be exchanged only between personal computers having the same software or navigation apparatuses made by the same manufacturer. Therefore, in the case of personal computers not having the same software and navigation apparatuses made by other manufacturers which are not compatible, it is impossible to use such route data. It is needless to say, that it is impossible to provide such route data to others who do not have the personal computer and navigation apparatus.

Brief Summary Text (7):

Further, even if not in possession of the navigation apparatus, if in possession of a portable personal computer with, for example, the same software, it is possible to be provided with such route data. However, in the case of not having the respective portable personal computer, it is impossible to be provided with such route data. This is similar in case of not only providing such route data to others

and but also wanting to use it for oneself. That is to say, in the case of having only a desk top type personal computer but not' having the portable personal computer, it is impossible to use such route data for oneself.

Brief Summary Text (8):

On one hand, some kinds of map display and the route searching software for personal computers are able to express such route data as to a sentence and to print out this sentence. If it is possible to print out the route guidance information like this, it is possible for others to be provided the route guidance information even if they do not have a personal computer with the same software and a navigation apparatus made by the same manufacturer nor a portable personal computer. However, in this case, it is hard for the user to intuitively understand the route guidance information, including the sentence mentioned above. Therefore, route guidance information which is easier to understand is desired.

Brief Summary Text (10):

The present invention is executed referring to the circumstances as mentioned above. An object of the present invention is to provide an apparatus, a method for providing map information and an information recording medium, all of which make it possible to provide easily understood and used searched route information without a navigation apparatus made by the same manufacturer or a portable personal computer.

Brief Summary Text (11):

The present invention, in order to solve the above mentioned problems, is characterized by extracting passing point information from a route between at least two points on map data, generating image data near a passing point according to the passing point information extracted, disposing the image data near the crossing point in order according to the route between two points and outputting it.

Brief Summary Text (12):

That is to say, according to the present invention, it is possible to provide easily understood searched route information without the same software in a personal computer nor a navigation apparatus made by the same manufacturer, nor a portable computer. This is accomplished by laying out an image at each passing point on the searched route in a fixed sequence and outputting the image.

Drawing Description Text (2):

FIG. 1 is a block diagram showing the whole structure of an apparatus for providing map information according to the present invention.

Drawing Description Text (3):

FIG. 2 is a flowchart showing flow of processing in an apparatus for providing map information according to the present invention.

Drawing Description Text (4):

FIG. 3 is a drawing showing an embodiment that a guidance and a navigation window are displayed on a display screen.

Drawing Description Text (6):

FIG. 5 is a drawing showing an embodiment of a rally map.

Detailed Description Text (3):

The structure of an embodiment of an apparatus for providing map information according to the present invention is shown in FIG. 1.

Detailed Description Text (6):

The hard disc 3 is provided for storing the OS and the application software and for recording/reproducing text, image, voice data and other types of file data. In the apparatus for providing map information according to the present invention, it is

also used for recording and reproducing the image data that amount of data is particularly large such as a map.

Detailed Description Text (8):

An input apparatus 2 includes a mouse, a keyboard, a touch switch and a pen input apparatus and converts input from a user to usable data inside the apparatus. In the apparatus for providing map information according to the present invention, input apparatus 2 is used for inputting the setting information of the appointed points, such as a starting point, destination and a passing place necessary for automatic route searching, and the setting of information regarding the calculation conditions of priority of distance, time, etc. for automatic route searching. The priority of distance means to automatically search, for example, for the shortest route and the priority of time means to automatically search for the route where the estimated necessary time is the shortest.

Detailed Description Text (9):

A disc drive apparatus 6 not only drives a disk type recording medium, such as a CD-ROM disk and a floppy disc, but also writes the data recorded in the respective disk type recording medium, writes the data when the respective disk type recording medium is recordable, etc. In the present embodiment, the CD-ROM disk (a map disc 30) on which digital map data is recorded is loaded in the disk drive apparatus 6, which reads the digital map data recorded on the map disk 30. On the map disk 30, not only the image data of the map but also information such as a distance on the map, legal limited speed, the number of signals on a road, the number of lanes on the road and a list of crossings, guide information for sightseeing a shopping guide, voice information for route guidance, other sound information, text information of characters, etc. are recorded. Further, disk -type recording medium includes not only the CD-ROM as mentioned above but also an optical disc such as DVD (digital video disk).

Detailed Description Text (10):

A data input/output port 9 includes not only, for example, a terminal for inputting/outputting digital data, but also, for example, an inserted part into which a semiconductor memory element such as a memory card is inserted, etc.. In the present embodiment, the data is inputted/outputted through, for example, the terminal for inputting/outputting the data and the memory card and to a portable electronic information terminal with a display through the data input/output port 9. The digital map data is supplied through not only the map disk 30 but also the data input/output port 9, for example, correspondence.

Detailed Description Text (11):

Any kind of display means such as, for example, a CRT (Cathode Ray Tube), a liquid crystal display and a plasma display is applied as a display apparatus 7, which generates an image signal according to the image and the text data generated as below mentioned and displays an image, a character and so on corresponding the image signal. The map image, and the character, etc. are mainly displayed on the display screen of the display apparatus 7 of the apparatus for providing map information according to the present embodiment.

Detailed Description Text (12):

A map viewing module 15 displays a wide area map on the display screen of the display apparatus 7 as the fundamental screen of the map display software used for the present embodiment. That is to say, it reads the wide area map data from the map disk 30 and displays it through display apparatus 7. The screen on which the representative wide area map is displayed is called a guidance window as follows. On the guidance window, it is possible to set, scroll and zoom (enlarge/contract) the information such as a starting place, a destination, etc. by, for example, using a mouse of the input apparatus 2.

Detailed Description Text (14):

The route calculating module 11 refers to each parameter about the distance information read from the map disk 30 and the road information (such as the legal limited speed, the number of signals, the number of lanes, one-way traffic and restricted information) and calculates the optimum route according to either calculating condition parameter of the priority of time or distance inputted from the input device 2 by automatically searching the route. Of course, it is also possible to calculate not only the route for a car but also the optimum route for a walking man and a running bicycle. In this case, a parameter such as the man's walking speed and bicycle's running speed is referred to from the map disc 30. Further, in case of finding the route for the man and the bicycle, it is possible to find the route through which a car can not pass.

Detailed Description Text (15):

A module 12 for generating navigation guidance generates all the information necessary for the navigation guidance of the respective route according to the route data calculated by the route calculating module 11. Substantially, the respective navigation guidance generating module 12 generates the picture data such as the enlarged picture of each crossing (a form of each crossing) necessary for the navigation guidance of the respective route, a land mark, a signal, an arrow showing the progressing direction and a road sign such as a restricted area and the guidance information necessary for the route guidance according to the route data calculated by the route calculating module 11 referring the map data recorded on the map disk 30. Further, the navigation guidance generating module 12 generates the information for displaying on the display screen by forming the window for displaying the enlarged picture (a navigation window) of the pop-upped crossing on the guidance window on which the wide area map is displayed. That is to say, then the navigation guidance generating module 12 constructs the information for displaying on the navigation window of each crossing displayed in order of the route referring to the picture data such as the enlarged picture of each crossing previously generated and the land mark and the guidance information. The guidance information includes, for example, position information of the crossing (an approximate position), a name of crossing, a distance between crossings, a name of road, the direction to go forward at each turning point, text information such as characters showing the land mark shown on the map, composite voice information in case of making a guidance about them by voice and so on. The picture data such as the enlarged map at each crossing and the guidance information are stored into the RAM 5 or the hard disc 3 once.

Detailed Description Text (16):

A rally map generating module 13 not only displays by pop-upping the navigation window on the guidance window on which the wide area map is shown according to the information supplied from the navigation guidance generating module 12, but also generates the information for displaying an icon used in choosing whether the enlarged picture of each crossing is necessary for the route navigation or not and displays it. Further, the respective rally map generating module 13 generates an image of the enlarged picture of each crossing chosen because it is necessary for the route navigation by the icon and the character line necessary for the route guidance are laid out easily to see, and the text information such as the name of position of each crossing displayed in order of the route as the additional information particularly necessary for the guidance of each crossing and the name of the previous crossing. Here, the image that the enlarged picture of each crossing and so on and the character line necessary for the route guidance are laid out means the image that the enlarged map of each crossing chosen. because it is necessary to reach the destination is laid out easily to see in order of the route and the character line such as the additional information for the guidance corresponding to each crossing is entered. The image laid out as above mentioned is called a rally map as follows. The rally map is made as a precondition to print as, for example, the size of A4 which is, for example, the standard of the size of paper of Japan Industrial Standard is in the longitudinal direction.

Detailed Description Text (17):

A printing module 14 generates printing data for printing longitudinally the respective rally map to, for example, paper of the size of A4 from data of the rally map generated by the rally map generating module 13.

Detailed Description Text (18):

A printer 20 prints longitudinally the rally map to a paper 21 of the size A4 according to the printing data supplied from the printing module 14.

Detailed Description Text (19):

The route calculating module 11, the navigation guidance generating module 12, the rally map generating module 13, the printing module 14 and the map viewing module 15 include software and are stored into the memory apparatus 10. The memory apparatus 10 includes, for example, the hard disk drive, the semiconductor memory, the CD ROM, etc., and may be the hard disk 3, the ROM 4, the RAM 5 or the map disk 30.

Detailed Description Text (20):

Next, in the apparatus for providing map information having the structure in FIG. 1, actuation from the automatic route searching to generating and printing of the rally map is realized along the flowchart shown in FIG. 2.

Detailed Description Text (21):

In the flowchart as shown in FIG. 2, at step ST1, the map viewing module 15 displays the wide area map on the display apparatus 7.

Detailed Description Text (22):

At the next step ST2, a user inputs settings corresponding to calculation conditions (e.g. whether a distance or time is a priority) from the input apparatus 2 by using the wide area map displayed as a guidance window and also inputs settings of the appointed point, such as a starting point, a destination and a passing place that are necessary for automatically searching the route.

Detailed Description Text (25):

At step ST5, the extracted optimum route data (that is to say, the data list of each crossing on the route) is transmitted to the navigation guidance generating module 12.

Detailed Description Text (26):

At step ST6, the navigation guidance generating module 12 generates all the information necessary for the navigation of the respective route according to the optimum route data calculated by the route calculating module 11. That is to say, the navigation guidance generating module 12 refers to the map data recorded on the map disk 30 and chooses each crossing particularly necessary for the navigation guidance from the list of each crossing of the optimum route obtained from the route calculating module 11, and extracts the picture data (such as the enlarged picture of each chosen crossing), the land mark, the signal, the arrow showing the proceeding direction and the road sign (such as the restricted area) and the guidance information necessary for the guidance of the route. Further, at step ST6, the navigation guidance generating module 12 generates the information for displaying the navigation window.

Detailed Description Text (27):

At step ST7, the list data of the crossing and the data necessary for the guidance chosen by the navigation guidance generating module 12, and the data for displaying the navigation window are transmitted to the rally map generating module 13.

Detailed Description Text (28):

At step ST8, the rally map generating module 13 collects the additional information necessary for the guidance of each crossing displayed in order of the route



according to the list data of each crossing chosen as it is necessary for the navigation and the guidance information necessary for the guidance.

Detailed Description Text (29):

At step ST9, the navigation window is displayed on the guidance window.

Detailed Description Text (30):

FIG. 3 shows one embodiment of a guidance window 101 and a navigation window 102 displayed on a display screen 100 of the display apparatus 7. That is to say, in FIG. 3, for example, the guidance window 101 is pop-upped on the display screen 100, in the guidance window 101. A number line 120 showing the wide area map, the name of the destination and the latitude and the longitude of the present displayed point are also displayed. The navigation window 102 is also pop-upped on the respective guidance window 101. In the navigation window 102, the enlarged map 106 of a crossing of each crossing is displayed in order of the route. Further, in the enlarged map 106 of the crossing of the navigation window 102, for example, the landmark 108 of "a police box" is displayed, further, the name of the road (in this embodiment, the character line 112 of "National Route 1"), the road sign mark 109 of the restricted area and the arrow mark 110 showing the progressing direction are also displayed. Outside of the respective enlarged map 106, the distance information from the crossing to the next crossing such as, for example, "500 m to the entrance of the industrial road" is displayed as the information to the next crossing, the words of, for example, "National Route 1" are displayed as the name of the road, the words of the name of the crossing ("No Name" because there is no name of the respective crossing in the embodiment in FIG. 3), and the words of, for example, "0.6 km" are displayed as the distance to the destination.

Detailed Description Text (31):

Further, in the navigation window 102, the icon 105 for directing whether choosing the enlarged map 106 of the respective crossing or not as the icon used in choosing whether the enlarged picture and so on of the respective crossing are necessary for the route navigation or not, the icon 104 for directing to go forward to the display of the navigation window corresponding to the next crossing and the icon 103 for directing to return to the display of the navigation window corresponding to the previous crossing are also displayed. The direction corresponding to each icon is executed by, for example, moving a mouse cursor on the icons 103, 104 and 105 and clicking.

Detailed Description Text (32):

That is to say, at step ST10 in FIG. 2, the operation information from the input apparatus 2 operated by the user of the respective apparatus for providing the map information, and the rally map generating module 13 chooses whether the enlarged image data and the guidance information of each crossing are necessary or not to know the route to reach the destination and registers the respective chosen crossing about the enlarged image of each crossing displayed in the navigation window in order of the route as above mentioned. Therefore, when it is not necessary, the registration of the respective crossing is not executed. The choice that the enlarged image data and the guidance information of each crossing are necessary for knowing the route to reach the destination is directed by user's clicking the icon 105. The detail of the choice processing of the crossing at the step ST10 is described below. When the enlarged image of each crossing displayed in order of the route is chosen at the step ST10, the respective rally map generating module 13 generates the rally map in which the word lines and so on necessary for the enlarged picture and so on of each crossing and the guidance are laid out. Though there are cases that the image of the rally map is displayed on the display screen, it must not be displayed.

Detailed Description Text (33):

At the next step ST11, it is judged whether or not the image of the rally map is printed or the image data of the respective rally map is outputted to, for example,

the portable electronic information terminal with the display.

Detailed Description Text (34):

When it is inputted by the input apparatus 2 to print, the image data of the rally map is transmitted to the printing module 14 at the step ST12 and the printing data is generated.

Detailed Description Text (36):

At step ST14, printing according to the respective printing data is executed by the printer 20 and the rally map is printed out to paper 21 of size A4.

Detailed Description Text (37):

On one hand, when it is judged to output the data at the step ST11, the image data of the rally map is transmitted to the data input/output port 9 at the step ST15.

Detailed Description Text (38):

At the step ST16, the image data of the rally map is outputted from the data input/output port and is transmitted to, for example, the portable electronic information terminal with the display.

Detailed Description Text (39):

Thus, it is possible to display the rally map on the display, of the respective portable electronic information terminal as shown at the step ST17 after that.

Detailed Description Text (46):

On one hand, in case of judging "YES" at the step ST24, proceed to the step ST25 and register as the data about the respective crossing is necessary for the rally map at the step ST25. Registration of the data of this rally map is substantially executed by storing into the RAM 5 or the hard disk 3. After that, return to the step ST22.

Detailed Description Text (48):

As the rally map printed on the paper 21 or displayed on the display of the portable electronic information terminal, for example, the rally map shown in FIG. 5 is given.

Detailed Description Text (49):

In FIG. 5, in a rally map 200, enlarged images 201 through 206 of, for example, chosen six crossings are laid out in order of the route. In each enlarged image, the number (Guide POINT NO.) showing the order that the respective crossing appears on the route respectively, the word line showing a name of crossing, a figure showing a distance from a starting point or the previous crossing, arrow marks showing the proceeding direction are illustrated and the land and the signal mark, a name of road and so on are illustrated as the occasion demands.

Detailed Description Text (50):

Referring to FIG. 5, the embodiment will be described in detail. In case of, for example, Guide Point NO.1, the enlarged map of the crossing of the respective Guide Point NO.1 shows the crossing called "Shimokoriya" at a distance from the starting point by 4 km and there are a signal and a post office as the landmark at the crossing. Further, at this crossing, it is shown to proceed from the lower side and change a course to the right at the respective crossing.

Detailed Description Text (51):

The next crossing is disposed, for example, under the figure of Guide POINT NO.1 as Guide POINT NO.2, the enlarged map of the respective crossing is at the distance of 3.4 km from the previous crossing (that is to say, the crossing of Guide POINT NO.1) and is called "Hirado," there is only the signal at this crossing, and it is shown to have to progress from the lower side of the figure and go straight on through the respective crossing.

Detailed Description Text (52):

The next crossing is disposed, for example, under the figure of Guide POINT NO.2 as Guide POINT NO.3, the enlarged map of the respective crossing is at the distance of 5 km from the previous crossing (the crossing of Guide POINT NO.2) and is called "Entrance of Higasgi Totsuka." There is only this signal at this crossing, and it is shown to have to progress along the road called "Nakahara Road" by which there is a gas station as the landmark when progressing from the lower side of the figure and changing a course to the right at the respective crossing.

Detailed Description Text (53):

Further, the next crossing is disposed, for example, at the right of the figure of Guide POINT NO. 1 as Guide POINT NO. 4, the enlarged map of the respective crossing is at the distance of 15 km from the previous crossing (the crossing of Guide POINT NO.3) and the respective crossing is the crossing that the right road of a crossroads is disposed in the slantedly upper direction to the progressing direction from the lower to the upper side of the figure. This crossing is called "In front of Kawakami Elementary School," there is only the signal at the respective crossing, and it is shown to have to progress along the road called "National Road NO. 1" by which there is a gas station as the landmark when progressing along the highway called "Nakahara Highway" from the lower to the upper side of the figure and changing a course in the slantedly upper right direction at the respective crossing.

Detailed Description Text (54):

The next crossing is disposed, for example, under the figure of Guide POINT NO. 4 as Guide POINT NO.5, the enlarged map of the respective crossing is at the distance of 20 km from the previous crossing (the crossing of Guide POINT NO. 4) and there is no name of the crossing. It is shown that there is to a police box" as the landmark at the respective crossing, the left side of the respective crossing is a restricted area, and it is shown to have to change the course to the right at the respective crossing when progressing along the road called "National Road NO.1" from the lower to the upper side of the figure and changing a course to the right at the respective crossing.

Detailed Description Text (55):

The next crossing is disposed, for example, under the figure of Guide POINT NO.5 as Guide POINT NO.6, the enlarged map of the respective crossing is at the distance of 0.5 km from the previous crossing (the crossing of Guide POINT NO.5) and this crossing is the T-type crossing called "The Entrance of the Industrial Road." It is shown that there is the destination after passing the respective crossing in the enlarged map when progressing from the lower to the upper side of the figure on the enlarged map.

Detailed Description Text (56):

Further, on the respective rally map, the date when the respective rally map was made and the names of the starting point and the destination are also entered.

Detailed Description Text (57):

The enlarged map of the crossing displayed on the navigation window 102 in FIG. 3 shows the embodiment in case that the enlarged image 205 of the crossing in FIG. 5 is displayed.

Detailed Description Text (58):

As above mentioned, in the apparatus for providing the map information of the embodiment according to the present invention, the rally map that the enlarged map of each crossing necessary for the route navigation and the guidance information are laid out in order of the route easily to see is printed out on a paper or are displayed on the display of the portable electronic information terminal. Therefore, even in the environment which is provided with the same map display and

the search software, it is possible to move to the destination, to expand widely the using range and to realize the original function of the personal computer application impossible for the conventional car navigation system by the user's carrying of the rally map (a print and so on). Further, as on the rally map the information is constructed as the enlarged map is main, it is possible to provide more intuitively it than the information of only words.

Detailed Description Text (59):

The rally map as above mentioned is an example, as the layout which is more easily to see, it is also possible to use other layout except one shown in FIG. 5. Further, it is also possible to use other wide area map displayed in the guidance window and the enlarged map of the crossing shown on the navigation window and the rally map, and to display to get a bird's-eye view of it. Further, it is possible to make the display and the illustrated map including the solid image which is almost a real thing.

Detailed Description Text (60):

Though in the embodiment as above mentioned, the rally map is generated by extracting the crossing information from the map data and displaying it as the enlarged map on the navigation window 102, the passing point may be extracted at each fixed distance from the route calculated by the route calculating module 11, the map data near the passing point may be cut down by the size of m.times.n from the wide area map data, the navigation window 102 may be displayed according to the map data near the passing point cut down and the rally map may be generated.

Detailed Description Text (61):

As it is clear as above mentioned, according to the present invention, it is possible to easily provide or use the searched route information even if the personal computer is not provided with the same software and you do not have the navigation apparatus made by the same manufacturer and the portable personal computer.

Other Reference Publication (2):

O'Leary, "Mapquest and Maps On Us: Top Web Map Services," Online, vol. 21, No. 5, Sep./Oct. 1997, pp. 56-58.

Other Reference Publication (3):

"Geosystems' MapQuest Unveils the Most Customizable Driving Directions Available on the Web," Geosystems Global Corporation press release, May 27, 1997, located at URL: <http://www.geosys.com/cgi-bin/genobject/pr.sub.-MQcustdirections/tig75b5>.

CLAIMS:

1. An apparatus for providing map information comprising:

an information extraction means for extracting necessary passing point information from an optimum route between at least two points on map data, the necessary passing point information including information necessary for route navigation;

an image generation means for generating image data near a necessary passing point according to the necessary passing point information;

an image disposing means for disposing the image data; and

an output control means for controlling output of images near the necessary passing point disposed by said means for disposing images.

2. The apparatus for providing map information according to claim 1, wherein said information extraction means extracts crossing information necessary for route navigation as said passing point information.

3. The apparatus for providing map information according to claim 1, wherein said image disposing means disposes the image data near the necessary passing point in order along the optimum route between at least two points on said map data.
4. The apparatus for providing map information according to claim 3, wherein said information extraction means extracts the necessary passing point information which is on the optimum route according to calculation of the route of shortest distance between at least two points on the map data.
5. The apparatus for providing map information according to claim 3, wherein said information extraction means extracts the necessary passing point information which is on the optimum route according to calculation of the route of shortest required time between at least two points on the map data.
6. The apparatus for providing map information according to claim 1, wherein said image disposing means disposes images near necessary passing points chosen by a user from images near plural necessary passing points generated by said image generation means.
7. The apparatus for providing map information according to claim 1, wherein said image generation means generates the image data such that route information is included in the image data.
8. The apparatus for providing map information according to claim 1, wherein said image disposing means disposes spatially the images near the necessary passing point on the same plane.
9. The apparatus for providing map information according to claim 8, wherein said output control means controls output for printing the images on paper.
10. The apparatus for providing map information according to claim 1, wherein said output control means controls output for transmitting image data to other terminal apparatus.
11. A method for providing map information comprising the steps of:  
  
extracting necessary passing point information from an optimum route between at least two points on map data, the necessary passing point information including information necessary for route navigation;  
  
generating image data near a necessary passing point according to the necessary passing point information extracted by said step for extracting information;  
  
disposing the image data near the necessary passing point; and  
  
controlling output of images near the necessary passing point disposed in the disposing step.
12. The method for providing map information according to claim 11, wherein said extracting step extracts crossing information necessary for route navigation as said passing point information.
13. The method for providing map information according to claim 11, wherein said disposing step disposes the image data near the necessary passing point in order along the optimum route between at least two points on said map data.
14. The method for providing map information according to claim 13, wherein said extracting step extracts the necessary passing point information which is on the optimum route according to calculation of the route of shortest distance between at

least two points on the map data.

15. The method for providing map information according to claim 13, wherein said extracting step extracts the necessary passing point information which is on the optimum route according to calculation of the route of shortest time required between at least two points on the map data.

16. The method for providing map information according to claim 11, wherein said disposing step disposes the images near necessary passing points chosen by a user from images near plural necessary passing points generated by said generating step.

17. The method for providing map information according to claim 11, wherein said generating step generates the images data such that route information is added to the image data near the passing point.

18. The method for providing map information according to claim 11, wherein said disposing step disposes spatially the images near the necessary passing point on the same plane.

19. The method for providing map information according to claim 18, wherein said output step controls output for printing on paper.

20. The method for providing map information according to claim 11, wherein said output control step controls output for transmitting data to other terminal apparatus.

21. A medium for recording information in which are recorded processing orders for:

extracting necessary passing point information from an optimum route between at least two points on map data, the necessary passing point information including information necessary for route navigation;

generating image data near a necessary passing point according to said necessary passing point information extracted;

disposing said image data near the necessary passing point generated in order according to said optimum route between two points; and

outputting disposed images near the necessary passing point.

[Previous Doc](#)

[Next Doc](#)

[Go to Doc#](#)

[First Hit](#) [Fwd Refs](#)[Previous Doc](#)[Next Doc](#)[Go to Doc#](#)

Generate Collection

Print

L23: Entry 2 of 3

File: USPT

Jun 10, 1997

US-PAT-NO: 5638116

DOCUMENT-IDENTIFIER: US 5638116 A

TITLE: Object recognition apparatus and method

DATE-ISSUED: June 10, 1997

## INVENTOR-INFORMATION:

NAME	CITY	STATE	ZIP CODE	COUNTRY
Shimoura; Hiroshi	Osaka			JP
Tenmoku; Kenji	Osaka			JP

US-CL-CURRENT: 348/118; 348/135, 348/169, 382/103

## ABSTRACT:

An object recognition apparatus that can recognize an object in an image acquired by an on-vehicle camera mounted on a vehicle with high efficiency and accuracy. A recognition processing is carried out in a cut off range, which is cut off from the image, and in which an object to be recognized is supposed to be present. The cut off range is obtained using support information supplied from a position detection device and/or an anti-lock brake device of the vehicle. Since the object in the image changes its position as the vehicle moves, the displacement must be estimated during the object recognition. The estimation requires camera attitude parameters of the on-vehicle camera with respect to the road, and the estimation is performed using support information supplied from the position detection device and/of the anti-lock brake device. This will improve the efficiency and accuracy of obtaining the camera attitude parameters.

31 Claims, 66 Drawing figures

Exemplary Claim Number: 1

Number of Drawing Sheets: 49

[Previous Doc](#)[Next Doc](#)[Go to Doc#](#)

[First Hit](#) [Fwd Refs](#)[Previous Doc](#)[Next Doc](#)[Go to Doc#](#)**End of Result Set**☐ [Generate Collection](#) [Print](#)

L23: Entry 3 of 3

File: USPT

Nov 28, 1995

US-PAT-NO: 5471205

DOCUMENT-IDENTIFIER: US 5471205 A

TITLE: Map displaying method

DATE-ISSUED: November 28, 1995

INVENTOR-INFORMATION:

NAME	CITY	STATE	ZIP CODE	COUNTRY
Izawa; Michio	Kohoku-ku, Yokohama, Kanagawa			JP

APPL-NO: 08/297549 [PALM]

DATE FILED: August 31, 1994

INT-CL-ISSUED: [06] G08G 1/123

INT-CL-CURRENT:

TYPE	IPC	DATE
CIPS	<u>G08 G 1/0969</u>	20060101
CIPS	<u>G01 C 21/34</u>	20060101
CIPS	<u>G01 C 21/36</u>	20060101
CIPS	<u>G09 B 29/10</u>	20060101

US-CL-ISSUED: 340/995; 340/990, 340/994, 340/988, 364/444, 364/449

US-CL-CURRENT: 340/995.27; 340/988, 340/990, 340/994, 701/208

FIELD-OF-CLASSIFICATION-SEARCH: 340/990, 340/995, 340/988, 340/994, 364/449, 364/518, 364/444

See application file for complete search history.

PRIOR-ART-DISCLOSED:

U.S. PATENT DOCUMENTS

[Search Selected](#) [Search ALL](#) [Clear](#)

	PAT-NO	ISSUE-DATE	PATENTEE-NAME	US-CL
<input type="checkbox"/>	<u>4419079</u>	December 1983	Georges et al.	340/995
<input type="checkbox"/>	<u>4845631</u>	July 1989	Bottorf	340/995
<input type="checkbox"/>	<u>4893127</u>	January 1990	Clark et al.	340/995



<input type="checkbox"/>	<u>4974170</u>	November 1990	Bouve et al.	340/995
<input type="checkbox"/>	<u>5212643</u>	May 1993	Yoshida	340/995
<input type="checkbox"/>	<u>5293163</u>	March 1994	Kakihara et al.	340/995

ART-UNIT: 267

PRIMARY-EXAMINER: Peng; John K.

ASSISTANT-EXAMINER: Lee; Benjamin C.

ATTY-AGENT-FIRM: Rogers & Killeen

ABSTRACT:

A display method for displaying one or more of the current point, the target point, or objective point on a display screen, the method suppressing a display of useless background and offering sufficient background for visual and geographical recognition of the displayed point. When displaying a map of an area about a display point, the displayed area is defined by a circular region having a predetermined radius and a fan-shaped region which spreads at a predetermined angle from a path to be followed by the current point.

19 Claims, 10 Drawing figures

[Previous Doc](#)

[Next Doc](#)

[Go to Doc#](#)